




SUPERNOVA LINE 65 TRIMLESS 930
DIM5
20628 9305



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 685
RECESSED DEPTH (MM)	200
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	7.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY

Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	8635lm // 58,8W // 147lm/W
LED TECHNICS (LUMINAIRE)	6165lm // 68W // 91lm/W

Options	
WIRELESS CONTROL DIM5	

For detailed installation instructions, please consult the manual: [20628_XXX5_HAND.pdf](#)


SUPERNOVA LINE 65 TRIMLESS 930 DIM5
 20628 9305

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-

FINISH YOUR SPECIFICATION

Miscellaneous control equipment

	300 90 004 ED5 WIRELESS CONTROL DIM5	☐
---	---	--------------------------

Notes: