



SPY 20 L ON 3 92730 B-B



27214 9220 B-B

AVAILABLE IN

BLACK-BLACK 27214 9220 B-B

FULL WHITE 27214 9220 FW

WHITE-WHITE 27214 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° INCL. LED POWER SUPPLY 24V-DC + CONVERTER 1000mA SPY 20 TUBE B included

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 2,9W / CRI>90 (R9: 55) / 2700K / 294lm)
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	882lm // 8,7W // 100lm/W
LED TECHNICS (LUMINAIRE)	665lm // 10W // 66lm/W

For detailed installation instructions, please consult the manual: [27214_XXX0_HAND.pdf](#)



SPY 20 L ON 3 92730 B-B

27214 9220 B-B

Notes: