





DOT.COM L4 ON 93032 W-B
 11525 9320 W-B

AVAILABLE IN
BLACK-BLACK 11525 9320 B-B
WHITE-BLACK 11525 9320 W-B




[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR FL-32° INCL.LED POWER SUPPLY 1050mA-DC
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 12,6W / CRI>90 (R9: 50) / 3000K / 1226lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1226lm // 12,6W // 97lm/W
LED TECHNICS (LUMINAIRE)	823lm // 14W // 57lm/W

For detailed installation instructions, please consult the manual: [11525_XXX0_HAND.pdf](#)



DOT.COM L4 ON 93032 W-B

11525 9320 W-B

Notes: