



ENTERO SQ-S TRIMLESS IP TW 96520 B

28552 9020 B



AVAILABLE IN

BLACK 28552 9020 B

FULL WHITE 28552 9020 FW

GOLD COLOURED 28552 9020 GC

WHITE 28552 9020 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	120
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.24
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	704lm // 10W // 68lm/W

Requirements

MOUNTING KIT ENTERO SQUARE S
LED POWER SUPPLY 500mA-DC TW (Remote)

ENTERO SQ-S TRIMLESS IP TW 96520 B

28552 9020 B

For detailed installation instructions, please consult the manual: [28552_XXX0_HAND.pdf](#)


CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT ENTERO SQ-S	Required
 Plasterboard	 MOUNTING KIT ENTERO SQ-S	Required
 Stucanet	 MOUNTING KIT ENTERO SQ-S	Required
 Wood	 MOUNTING KIT ENTERO SQ-S	Required
 Concrete + plaster	 MOUNTING KIT ENTERO SQ-S	Required
 Lintel + plaster	 MOUNTING KIT ENTERO SQ-S	Required
 Hollow-core slab + plaster	 MOUNTING KIT ENTERO SQ-S	Required
 Stretched ceiling	 MOUNTING KIT ENTERO SQ-S CSC	Required
	 MOUNTING KIT ENTERO SQ-S WSC	Required

ENTERO SQ-S TRIMLESS IP TW 96520 B
28552 9020 B

FINISH YOUR SPECIFICATION


LED power supplies #



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2 ☐


Mounting kits



28400 0040 MOUNTING KIT ENTERO SQ-S

☐

Mounting kits stretched ceiling



28400 0100 MOUNTING KIT ENTERO SQ-S CSC

☐




28400 0160 MOUNTING KIT ENTERO SQ-S WSC

☐

ENTERO SQ-S TRIMLESS IP TW 96520 B
28552 9020 B

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: