



ENTERO RD-M TRIMLESS SOFT 93018 B

28431 9010 B



AVAILABLE IN

BLACK 28431 9010 B

FULL WHITE 28431 9010 FW

GOLD COLOURED 28431 9010 GC

WHITE 28431 9010 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCLDIMMABLE LED POWER SUPPLY 450mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,1W / CRI>90 (R9: 50) / 3000K-1800K / 1618lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1618lm // 16,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	1190lm // 19W // 64lm/W

Requirements

MOUNTING KIT ENTERO ROUND M
LED POWER SUPPLY 450mA-DC DIM (Remote)

ENTERO RD-M TRIMLESS SOFT 93018 B

28431 9010 B

Accessories

- ENTERO M HONEYCOMB
- ENTERO M LINEAR SPREAD LENS
- ENTERO M SPREAD LENS
- ENTERO M SOFTENING LENS
- ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28431_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Wood	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT ENTERO RD-M CSC	Required
	 MOUNTING KIT ENTERO RD-M WSC	Required

ENTERO RD-M TRIMLESS SOFT 93018 B

28431 9010 B






FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

LED power supplies


#

	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1(0) ☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(0) ☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(0) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1 ☐

ENTERO RD-M TRIMLESS SOFT 93018 B

28431 9010 B


Mounting kits



28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.



Mounting kits stretched ceiling



28400 0080 MOUNTING KIT ENTERO RD-M CSC









28400 0140 MOUNTING KIT ENTERO RD-M WSC



ENTERO RD-M TRIMLESS SOFT 93018 B
 28431 9010 B

Light altering devices

	28500 0070	ENTERO M LINEAR SPREAD LENS	☐
	28500 0080	ENTERO M SPREAD LENS	☐
	28500 0090	ENTERO M SOFTENING LENS	☐
	28500 0100	ENTERO M GLASS SBL	☐
	28500 0110 B	ENTERO M HONEYCOMB SINGLE USE B	☐
	28500 0120 B	ENTERO M HONEYCOMB DOUBLE USE B	☐

 DELTALIGHT®

ENTERO RD-M TRIMLESS SOFT 93018 B

28431 9010 B

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐
	24611 0240 SPY 66 REFLECTOR 45°	☐

Notes: