



ENTERO SQ-M TRIMLESS SOFT 93018 B

28531 9010 B



AVAILABLE IN

BLACK 28531 9010 B

FULL WHITE 28531 9010 FW

GOLD COLOURED 28531 9010 GC

WHITE 28531 9010 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.405
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCLDIMMABLE LED POWER SUPPLY 450mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,1W / CRI>90 (R9: 50) / 3000K-1800K / 1618lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1618lm // 16,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	1229lm // 19W // 66lm/W

Requirements

MOUNTING KIT ENTERO SQUARE M
LED POWER SUPPLY 450mA-DC DIM (Remote)

ENTERO SQ-M TRIMLESS SOFT 93018 B

28531 9010 B

Accessories

- ENTERO M HONEYCOMB
- ENTERO M LINEAR SPREAD LENS
- ENTERO M SPREAD LENS
- ENTERO M SOFTENING LENS
- ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28531_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit		
 System ceiling		MOUNTING KIT ENTERO SQ-M	Required
 Plasterboard		MOUNTING KIT ENTERO SQ-M	Required
 Stucanet		MOUNTING KIT ENTERO SQ-M	Required
 Wood		MOUNTING KIT ENTERO SQ-M	Required
 Concrete + plaster		MOUNTING KIT ENTERO SQ-M	Required
 Lintel + plaster		MOUNTING KIT ENTERO SQ-M	Required
 Hollow-core slab + plaster		MOUNTING KIT ENTERO SQ-M	Required
 Stretched ceiling		MOUNTING KIT ENTERO SQ-M CSC	Required
		MOUNTING KIT ENTERO SQ-M WSC	Required

ENTERO SQ-M TRIMLESS SOFT 93018 B

28531 9010 B






FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

LED power supplies

#


	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1(0) ☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(0) ☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(0) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1 ☐

 DELTALIGHT®

ENTERO SQ-M TRIMLESS SOFT 93018 B

28531 9010 B

Mounting kits




28400 0050

MOUNTING KIT ENTERO SQ-M

☐


Mounting kits stretched ceiling



28400 0110

MOUNTING KIT ENTERO SQ-M CSC

☐



28400 0170

MOUNTING KIT ENTERO SQ-M WSC







☐

 DELTALIGHT®

ENTERO SQ-M TRIMLESS SOFT 93018 B

28531 9010 B

Light altering devices

	28500 0070 ENTERO M LINEAR SPREAD LENS	☐
	28500 0080 ENTERO M SPREAD LENS	☐
	28500 0090 ENTERO M SOFTENING LENS	☐
	28500 0100 ENTERO M GLASS SBL	☐
	28500 0110 B ENTERO M HONEYCOMB SINGLE USE B	☐
	28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B	☐

✕ DELTALIGHT®

ENTERO SQ-M TRIMLESS SOFT 93018 B

28531 9010 B

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐
	24611 0240 SPY 66 REFLECTOR 45°	☐

Notes: