



ENTERO SQ-M TRIMLESS IP TW 96518 B

28555 9010 B



AVAILABLE IN

BLACK 28555 9010 B

FULL WHITE 28555 9010 FW

GOLD COLOURED 28555 9010 GC

WHITE 28555 9010 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	150
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.405
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	708lm // 10W // 68lm/W

Requirements

MOUNTING KIT ENTERO SQUARE M
LED POWER SUPPLY 500mA-DC TW (Remote)

ENTERO SQ-M TRIMLESS IP TW 96518 B

28555 9010 B

For detailed installation instructions, please consult the manual: [28555_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT ENTERO SQ-M	Required
 Plasterboard	 MOUNTING KIT ENTERO SQ-M	Required
 Stucanet	 MOUNTING KIT ENTERO SQ-M	Required
 Wood	 MOUNTING KIT ENTERO SQ-M	Required
 Concrete + plaster	 MOUNTING KIT ENTERO SQ-M	Required
 Lintel + plaster	 MOUNTING KIT ENTERO SQ-M	Required
 Hollow-core slab + plaster	 MOUNTING KIT ENTERO SQ-M	Required
 Stretched ceiling	 MOUNTING KIT ENTERO SQ-M CSC	Required
	 MOUNTING KIT ENTERO SQ-M WSC	Required


ENTERO SQ-M TRIMLESS IP TW 96518 B

28555 9010 B

FINISH YOUR SPECIFICATION

LED power supplies

#




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2

☐


Mounting kits



28400 0050 MOUNTING KIT ENTERO SQ-M

☐

Mounting kits stretched ceiling



28400 0110 MOUNTING KIT ENTERO SQ-M CSC

☐

28400 0170 MOUNTING KIT ENTERO SQ-M WSC

☐

Notes: