



ENTERO RD-M IP TW 96518 B

28416 9010 B



AVAILABLE IN

BLACK 28416 9010 B

FULL WHITE 28416 9010 FW

GOLD COLOURED 28416 9010 GC

WHITE 28416 9010 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 92
RECESSED DEPTH (MM)	145
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.415
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	725lm // 10W // 70lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Options

ENTERO RD-M MOUNTING SET S2

ENTERO RD-M IP TW 96518 B

28416 9010 B

For detailed installation instructions, please consult the manual: [28416_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 ENTERO RD-M MOUNTING SET S2 Required
 Concrete + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Lintel + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Stretched ceiling	-


ENTERO RD-M IP TW 96518 B

28416 9010 B

FINISH YOUR SPECIFICATION

LED power supplies

#




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2

☐

Mounting set S2



28500 0200 ENTERO RD-M MOUNTING SET S2

☐

Notes: