




ENTERO SQ-L X TW 96518 B
28549 9010 B

AVAILABLE IN
BLACK 28549 9010 B
FLEMISH BRONZE OUTDOOR 28549 9010 FBRX
FULL WHITE 28549 9010 FW
ANTHRACITE (DARK GREY) 28549 9010 N
WHITE 28549 9010 W



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 112 x 112
RECESSED DEPTH (MM)	175
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.77
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1418lm // 20W // 69lm/W

Requirements
LED POWER SUPPLY 500mA-DC TW

ENTERO SQ-L X TW 96518 B
28549 9010 B

Accessories

- ENTERO L HONEYCOMB
- ENTERO L LINEAR SPREAD LENS
- ENTERO L SPREAD LENS
- ENTERO L SOFTENING LENS
- ENTERO L GLASS SBL

For detailed installation instructions, please consult the manual: [28549_XXX0_HAND.pdf](#)


CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

ENTERO SQ-L X TW 96518 B
28549 9010 B

FINISH YOUR SPECIFICATION


LED power supplies #




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1 ☐


Light altering devices




28500 0130 ENTERO L LINEAR SPREAD LENS

☐


28500 0140 ENTERO L SPREAD LENS

☐

28500 0150 ENTERO L SOFTENING LENS

☐

28500 0160 ENTERO L GLASS SBL

☐

28500 0170 B ENTERO L HONEYCOMB SINGLE USE B

☐

Notes: