





**OCTAV 39 ON 1 92720 DIM8 B-B**  
29018 9228 B-B

AVAILABLE IN  
**BLACK-BLACK** 29018 9228 B-B  
**WHITE-WHITE** 29018 9228 W-W



 [View on website](#)

**General info**

|                           |                                                                                                                 |
|---------------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                          |
| <b>INSTALLATION</b>       | Ceiling Surface mounted                                                                                         |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                            |
| <b>WEIGHT (KG)</b>        | 0.5                                                                                                             |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 355° rotatable                                                                             |
| <b>INFORMATION</b>        | REFLECTOR FL-20°<br>INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC<br>Current selection via jumper on power supply |

**Electrical info**

|                     |                       |
|---------------------|-----------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz    |
| <b>CLASS</b>        | I                     |
| <b>POWER SUPPLY</b> | YES                   |
| <b>DIM TYPE</b>     | mains (phase cut-off) |
| <b>ENERGY CLASS</b> | E                     |

**Lightsource info**

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                  |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1041lm // 8,6W // 121lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 652lm // 10W // 66lm/W                            |

**Requirements**

SPY 39 LTUBE


For detailed installation instructions, please consult the manual: [29018\\_XXX8\\_HAND.pdf](#)

OCTAV 39 ON 1 92720 DIM8 B-B

29018 9228 B-B

FINISH YOUR SPECIFICATION

Finish your product

|                                                                                  |                              |                   |                          |
|----------------------------------------------------------------------------------|------------------------------|-------------------|--------------------------|
|  | <b><u>24144 0020 B</u></b>   | SPY 39 L TUBE B   | <input type="checkbox"/> |
|                                                                                  | <b><u>24144 0020 FBR</u></b> | SPY 39 L TUBE FBR | <input type="checkbox"/> |
|                                                                                  | <b><u>24144 0020 FG</u></b>  | SPY 39 L TUBE FG  | <input type="checkbox"/> |
|                                                                                  | <b><u>24144 0020 GC</u></b>  | SPY 39 L TUBE GC  | <input type="checkbox"/> |
|                                                                                  | <b><u>24144 0020 W</u></b>   | SPY 39 L TUBE W   | <input type="checkbox"/> |

Notes: