





M26L - SPY 52 WALLWASH 927 MDL B

19887 9200 B

AVAILABLE IN
BLACK 19887 9200 B
FLEMISH BRONZE 19887 9200 FBR
FLEMISH GOLD 19887 9200 FG
GOLD COLOURED 19887 9200 GC
WHITE 19887 9200 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	WALLWASH LENS EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	491lm // 10W // 50lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

LED POWER SUPPLY 48V-DC

M26L - SPY 52 WALLWASH 927 MDL B

19887 9200 B

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual: [19887_XXX0_HAND.pdf](#)

M26L - SPY 52 WALLWASH 927 MDL B

19887 9200 B

FINISH YOUR SPECIFICATION

Current supply

#



21032 0030 SMART 48 MODULATOR PLUG-IN WD

19

SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

19



300 90 012 SMART 48 MODULATOR WD

19


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20


M26L - SPY 52 WALLWASH 927 MDL B

19887 9200 B


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: