



D-LINER 30 SBL SAPP 13 RD 930 B

29213 9300 B

AVAILABLE IN

BLACK 29213 9300 B

WHITE 29213 9300 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 1250mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 1m + WIELAND PLUG 2 POLE INCL.2 x SUSPENSION BRACKET SAPP

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 45W / CRI>90 (R9: 57) / 3000K / 5687lm
SDCM	SDCM2
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	5687lm // 45W // 126lm/W
LED TECHNICS (LUMINAIRE)	4263lm // 52W // 82lm/W

Requirements

INFORM POWER SUPPLY 75W (DIM5)

For detailed installation instructions, please consult the manual: [29213_XXX0_HAND.pdf](#)

D-LINER 30 SBL SAPP 13 RD 930 B


29213 9300 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	Acoustic climate-control ceiling SAPP -

FINISH YOUR SPECIFICATION

LED power supplies	#
--------------------	---

	25510 0085 INFORM POWER SUPPLY 75W DIM5	1 ☐
--	--	----------------------------

Notes: