





D-LINER 30 SBL SAPP 11 930 DIM5 B

29215 9305 B

AVAILABLE IN

BLACK 29215 9305 B

WHITE 29215 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 1000mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 1m + WIELAND PLUG 5 POLE INCL.2 x SUSPENSION BRACKET SAPP

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 36W / CRI>90 (R9: 57) / 3000K / 4550lm
SDCM	SDCM2
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	4550lm // 36W // 126lm/W
LED TECHNICS (LUMINAIRE)	3410lm // 41W // 82lm/W

For detailed installation instructions, please consult the manual: [29215_XXX5_HAND.pdf](#)

D-LINER 30 SBL SAPP 11 930 DIM5 B
29215 9305 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling SAPP	-

Notes: