




M - DALI PRESENCE AND
DAYLIGHT SENSOR (BROADCAST)
21032 0185



 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
INFORMATION	PRESENCE and DAYLIGHT 0,1W max.

Electrical info

CLASS	III
-------	-----

For detailed installation instructions, please consult the manual: [21032_0185_HAND.pdf](#)

WHERE USED

420 20 10 00	SPM20 - PROFILE 1m
420 20 20 00	SPM20 - PROFILE 2m
420 20 30 00	SPM20 - PROFILE 3m
420 52 10 00	SPM52 - PROFILE 1m
420 52 20 00	SPM52 - PROFILE 2m
420 52 30 00	SPM52 - PROFILE 3m
23301 0000	SPM20 - PROFILE
23358 0000	SLM26L - PROFILE
23358 0010	SLM26L - PROFILE 1m
23358 0020	SLM26L - PROFILE 2m
23358 0030	SLM26L - PROFILE 3m
23359 0000	SLM26H - PROFILE
23359 0010	SLM26H - PROFILE 1m
23359 0020	SLM26H - PROFILE 2m
23359 0030	SLM26H - PROFILE 3m
23397 0000	SPM20 ST - PROFILE
23397 0020	SPM20 ST - PROFILE 2m
23397 0030	SPM20 ST - PROFILE 3m
24413 0000	SPM52 - PROFILE

M - DALI PRESENCE AND DAYLIGHT SENSOR (BROADCAST)

21032 0185

Notes: