




MOUNTING KIT SIDE AIR 103

29810 0030



 [View on website](#)

General info

LOCATION	indoor
CUTOUT SHAPE/SIZE (MM)	round - 168
RECESSED DEPTH (MM)	160
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
WEIGHT (KG)	0.29
INFORMATION	Supply flow rate: max. 25m ³ /h Extraction flow rate: max. 50m ³ /h For flexible tubes Ø100mm

For detailed installation instructions, please consult the manual: [29810_0030_HAND.pdf](#)

WHERE USED

19807 9220	SPY 52 TRIMLESS HE 92720
19807 9230	SPY 52 TRIMLESS HE 92740
19807 9320	SPY 52 TRIMLESS HE 93020
19807 9330	SPY 52 TRIMLESS HE 93040
19807 9420	SPY 52 TRIMLESS HE 94020
19807 9430	SPY 52 TRIMLESS HE 94040
19811 9220	SPY 52 TRIMLESS 92720
19811 9230	SPY 52 TRIMLESS 92745
19811 9240	SPY 52 TRIMLESS 92730
19811 9320	SPY 52 TRIMLESS 93020
19811 9330	SPY 52 TRIMLESS 93045
19811 9340	SPY 52 TRIMLESS 93030
19813 9020	SPY 52 TRIMLESS TW 96520
19813 9030	SPY 52 TRIMLESS TW 96545
19813 9040	SPY 52 TRIMLESS TW 96530
24121 9220	SPY 39 TRIMLESS 92720
24121 9230	SPY 39 TRIMLESS 92740
24121 9320	SPY 39 TRIMLESS 93020
24121 9330	SPY 39 TRIMLESS 93040
24180 9020	SPY 39 TRIMLESS SOFT 93020
24180 9030	SPY 39 TRIMLESS SOFT 93040



MOUNTING KIT SIDE AIR 103

29810 0030

Notes: