


SPM20 - AIR KIT 1

29810 1010



 [View on website](#)

General info

LOCATION	indoor
CUTOUT SHAPE/SIZE (MM)	rectangle - 50 x 310
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	min.9,5 - max.16
WEIGHT (KG)	0.62
INFORMATION	Supply flow rate: max. 25m ³ /h Extraction flow rate: max. 50m ³ /h For flexible tubes Ø100mm

Options

SPM20 - AIR KIT 1 ADAPTER SET

For detailed installation instructions, please consult the manual: [29810_1010_HAND.pdf](#)

WHERE USED

420 20 10 00	SPM20 - PROFILE 1m
420 20 20 00	SPM20 - PROFILE 2m
420 20 30 00	SPM20 - PROFILE 3m
23301 0000	SPM20 - PROFILE
29811 9220	SPM20 - JUM-OH! 4R AIR 92730
29811 9320	SPM20 - JUM-OH! 4R AIR 93030
29813 9220	SPM20 - SPY 392 AIR 92720
29813 9230	SPM20 - SPY 392 AIR 92740
29813 9320	SPM20 - SPY 392 AIR 93020
29813 9330	SPM20 - SPY 392 AIR 93040
29815 9220	SPM20 - SPY 522 AIR 92720
29815 9230	SPM20 - SPY 522 AIR 92745
29815 9240	SPM20 - SPY 522 AIR 92730
29815 9320	SPM20 - SPY 522 AIR 93020
29815 9330	SPM20 - SPY 522 AIR 93045
29815 9340	SPM20 - SPY 522 AIR 93030



SPM20 - AIR KIT 1

29810 1010

Notes: