





iMAX II ROUND ADJUSTABLE TRIMLESS SOFT 93045

24231 9030-R



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	160
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,8W / CRI>90 (R9: 50) / 3000K-1800K / 1307lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1307lm // 11,8W // 110lm/W
LED TECHNICS (LUMINAIRE)	782lm // 14W // 58lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM (Remote)
MOUNTING KIT R102 TRIMLESS O.F.A.
iMAX II TUBE TRIMLESS

For detailed installation instructions, please consult the manual: [24231_XXX0-R_HAND.pdf](#)

 DELTALIGHT®

iMAX II ROUND ADJUSTABLE TRIMLESS SOFT 93045

24231 9030-R

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit		
 System ceiling		MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Plasterboard		MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Concrete + plaster		MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Lintel + plaster		MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster		MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Stretched ceiling		MOUNTING KIT R102 TRIMLESS CSC	Required
		MOUNTING KIT R102 TRIMLESS WSC	Required

FINISH YOUR SPECIFICATION

Technical drawing of the 3D-printed part, showing dimensions: 25, 180, 45, 55, Ø33, 30, and 58.

21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

9










21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

7

 DELTALIGHT®


iMAX II ROUND ADJUSTABLE TRIMLESS SOFT 93045

24231 9030-R

LED power supplies			#
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	1->2(2) ☐
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	1(1) ☐
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	1->3(3) ☐
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	1(1) ☐
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) ☐
	21012 0021	LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035	LED POWER SUPPLY MULTI POWER DIM5	1 ☐
	21012 005W	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1 ☐
	21012 0268	LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	1 ☐


iMAX II ROUND ADJUSTABLE TRIMLESS SOFT 93045

24231 9030-R



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1


☐


21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

☐


Mounting kits




15212 2010 MOUNTING KIT R102 TRIMLESS O.F.A.

☐

Mounting kits stretched ceiling




15212 0090 MOUNTING KIT R102 TRIMLESS CSC

☐


15212 0170 MOUNTING KIT R102 TRIMLESS WSC

☐

Finish your product



24213 0020 B iMAX II TUBE ROUND TRIMLESS B

☐

24213 0020 FG iMAX II TUBE ROUND TRIMLESS FG

☐

24213 0020 W iMAX II TUBE ROUND TRIMLESS W

☐

iMAX II ROUND ADJUSTABLE TRIMLESS SOFT 93045

24231 9030-R

Notes: