



BOXY L SOFT 93045 DIM8 B-B

10744 9038 B-B



AVAILABLE IN

BLACK-BLACK 10744 9038 B-B

BLACK-FLEMISH BRONZE 10744 9038 B-FBR

BLACK-FLEMISH GOLD 10744 9038 B-FG

WHITE-WHITE 10744 9038 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.DIMMABLE POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	805lm // 12W // 69lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

For detailed installation instructions, please consult the manual: [10744_XXX8_HAND.pdf](#)

BOXY L SOFT 93045 DIM8 B-B

10744 9038 B-B

FINISH YOUR SPECIFICATION

Light altering devices

 Ø40	251 70 03 01 B BOXY HONEYCOMB B	☐
 Ø45 1.5		
	251 70 03 01 W BOXY HONEYCOMB W	☐
 Ø40	251 70 03 04 B BOXY SOFTENING LENS B	☐
 Ø45 1.5		
	251 70 03 04 W BOXY SOFTENING LENS W	☐
 Ø40	251 70 03 05 B BOXY GLASS SBL B	☐
 Ø45 1.5		
	251 70 03 05 W BOXY GLASS SBL W	☐

Notes: