





SPY 52 ST SOFT 93020 W-W

19897 9020 W-W

AVAILABLE IN
WHITE-WHITE 19897 9020 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 98
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	650lm // 12W // 55lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 500mA-DC DIM

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42

GLASS SBL 42
Delta Light NV may revise the information and technical data at any time without notice. Version: 24/02/2025

SPY 52 ST SOFT 93020 W-W
 19897 9020 W-W

For detailed installation instructions, please consult the manual: [19897_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Stretched ceiling	-

SPY 52 ST SOFT 93020 W-W

19897 9020 W-W

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B








☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐





SPY 52 ST SOFT 93020 W-W

19897 9020 W-W

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->3(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	1->5(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2	☐

SPY 52 ST SOFT 93020 W-W

19897 9020 W-W






	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1->2	☐

 DELTALIGHT®

SPY 52 ST SOFT 93020 W-W

19897 9020 W-W

Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	19810 0020 LINEAR SPREAD LENS 42	☐
	19810 0030 SPREAD LENS 42	☐
	19810 0040 SOFTENING LENS 42	☐
	19810 0050 GLASS SBL 42	☐
	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐



SPY 52 ST SOFT 93020 W-W

19897 9020 W-W

Finish your product

	40 19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

Replaceable reflector / lens

	18 19810 0180 SPY 52 REFLECTOR 20°	☐
	18 19810 0190 SPY 52 REFLECTOR 45°	☐
	18 19810 0240 SPY 52 REFLECTOR 30°	☐

Notes: