



SPY 52 CLIP SOFT 93020 B-B

19898 9020 B-B

AVAILABLE IN

BLACK-BLACK 19898 9020 B-B



FLEMISH BRONZE-BLACK 19898 9020 FBR-B

FLEMISH GOLD-BLACK 19898 9020 FG-B

FULL WHITE 19898 9020 FW

GOLD COLORED-BLACK 19898 9020 GC-B

WHITE-WHITE 19898 9020 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed,Ceiling Surface mounted
CUTOUT SHAPE/SIZE (MM)	round - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLDIMMABLE LED POWER SUPPLY 500mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	650lm // 12W // 55lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 500mA-DC DIM

Options

MOUNTING KIT FLUSH SPY

SPY 52 CLIP SOFT 93020 B-B

19898 9020 B-B

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual: [19898_XXX0_HAND.pdf](#)










CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 MOUNTING KIT FLUSH SPY Required
 Plasterboard	 MOUNTING KIT FLUSH SPY Required
 Stucanet	 MOUNTING KIT FLUSH SPY Required
 Wood	-
 Concrete	-
 Concrete + plaster	 MOUNTING KIT FLUSH SPY Required
 Lintel + plaster	 MOUNTING KIT FLUSH SPY Required
 Hollow-core slab	-
 Hollow-core slab + plaster	 MOUNTING KIT FLUSH SPY Required
 Stretched ceiling	-

SPY 52 CLIP SOFT 93020 B-B





19898 9020 B-B

FINISH YOUR SPECIFICATION


LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->3(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	1->5(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2	☐

SPY 52 CLIP SOFT 93020 B-B

19898 9020 B-B

	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1->2	☐

Mounting kits






	414 90 01 MOUNTING KIT FLUSH SPY		☐
--	---	--	--------------------------

 DELTALIGHT®

SPY 52 CLIP SOFT 93020 B-B

19898 9020 B-B

Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	19810 0020 LINEAR SPREAD LENS 42	☐
	19810 0030 SPREAD LENS 42	☐
	19810 0040 SOFTENING LENS 42	☐
	19810 0050 GLASS SBL 42	☐
	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐




SPY 52 CLIP SOFT 93020 B-B

19898 9020 B-B

Finish your product

 40 Ø49	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

Replaceable reflector / lens

 18 Ø45	19810 0180 SPY 52 REFLECTOR 20°	☐
 18 Ø45	19810 0190 SPY 52 REFLECTOR 45°	☐
 18 Ø45	19810 0240 SPY 52 REFLECTOR 30°	☐

Notes: