



ENTERO RD-S X SOFT 93020 B

28483 9020 B

AVAILABLE IN



BLACK 28483 9020 B

FLEMISH BRONZE OUTDOOR 28483 9020 FBRX

FULL WHITE 28483 9020 FW

ANTHRACITE (DARK GREY) 28483 9020 N

WHITE 28483 9020 W



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	110
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.28
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	626lm // 12W // 53lm/W

Requirements

LED POWER SUPPLY 500mA-DC DIM

Options

ENTERO RD-S MOUNTING SET S2

ENTERO RD-S X SOFT 93020 B

28483 9020 B


Accessories

ENTERO S HONEYCOMB
ENTERO S LINEAR SPREAD LENS
ENTERO S SPREAD LENS
ENTERO S SOFTENING LENS
ENTERO S GLASS SBL

For detailed installation instructions, please consult the manual: [28483_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY










Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 ENTERO RD-S MOUNTING SET S2 Required
 Concrete + plaster	 ENTERO RD-S MOUNTING SET S2 Required
 Lintel + plaster	 ENTERO RD-S MOUNTING SET S2 Required
 Hollow-core slab	 ENTERO RD-S MOUNTING SET S2 Required
 Hollow-core slab + plaster	 ENTERO RD-S MOUNTING SET S2 Required
 Stretched ceiling	-



9


7

ENTERO RD-S X SOFT 93020 B
 28483 9020 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->3(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	1->5(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2	☐


ENTERO RD-S X SOFT 93020 B

28483 9020 B




21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1 ☐




21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2 ☐



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1 ☐



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1->2 ☐

Light altering devices



28500 0010 ENTERO S LINEAR SPREAD LENS

☐



28500 0020 ENTERO S SPREAD LENS

☐




28500 0030 ENTERO S SOFTENING LENS

☐



28500 0040 ENTERO S GLASS SBL

☐




28500 0050 B ENTERO S HONEYCOMB SINGLE USE B

☐


ENTERO RD-S X SOFT 93020 B

28483 9020 B


Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Mounting set S2



28500 0190 ENTERO RD-S MOUNTING SET S2

☐

Notes: