



ENTERO SQ-S SOFT 93020 B

28580 9020 B



AVAILABLE IN

BLACK 28580 9020 B

FULL WHITE 28580 9020 FW

GOLD COLOURED 28580 9020 GC

WHITE 28580 9020 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 76 x 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.24
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	807lm // 12W // 69lm/W

Requirements

LED POWER SUPPLY 500mA-DC DIM

ENTERO SQ-S SOFT 93020 B
28580 9020 B

Accessories

- ENTERO S HONEYCOMB
- ENTERO S LINEAR SPREAD LENS
- ENTERO S SPREAD LENS
- ENTERO S SOFTENING LENS
- ENTERO S GLASS SBL

For detailed installation instructions, please consult the manual: [28580_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

ENTERO SQ-S SOFT 93020 B

28580 9020 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

☐










21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐





 DELTALIGHT®

ENTERO SQ-S SOFT 93020 B

28580 9020 B

LED power supplies			#
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	1->3(3) ☐
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) ☐
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	1->5(3) ☐
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	1(1) ☐
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) ☐
	21012 0010	LED POWER SUPPLY MULTI POWER	1->2 ☐
	21012 0021	LED POWER SUPPLY MULTI POWER DIM1	1->2 ☐
	21012 0035	LED POWER SUPPLY MULTI POWER DIM5	1->2 ☐
	21012 005W	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 ☐




ENTERO SQ-S SOFT 93020 B
28580 9020 B

	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 ☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1 ☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1->2 ☐

 DELTALIGHT®


ENTERO SQ-S SOFT 93020 B
28580 9020 B

Light altering devices

	28500 0010	ENTERO S LINEAR SPREAD LENS	☐
	28500 0020	ENTERO S SPREAD LENS	☐
	28500 0030	ENTERO S SOFTENING LENS	☐
	28500 0040	ENTERO S GLASS SBL	☐
	28500 0050 B	ENTERO S HONEYCOMB SINGLE USE B	☐
	28500 0060 B	ENTERO S HONEYCOMB DOUBLE USE B	☐

ENTERO SQ-S SOFT 93020 B
28580 9020 B

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: