





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 320 DOWN TW 1 DT8 85063 DIM5 B-B 30715 8035 B-B

AVAILABLE IN
BLACK-BLACK 30715 8035 B-B
WHITE-BLACK 30715 8035 W-B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) EXCL.CABLE SUSPENSION MELANOPIC LIGHT TECHNOLOGY

Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 2701lm // 34W // 79lm/W Or @ 5000K: 3233lm // 31W // 104lm/W

Options	
INF40 SQ 320/360 - SUSPENSION SET CABLE BASE R / S	



INFORM 40 SQ 320 DOWN TW 1 DT8 85063 DIM5 B-B

30715 8035 B-B


For detailed installation instructions, please consult the manual: [**30715_XXX5_HAND.pdf**](#)

INFORM 40 SQ 320 DOWN TW 1 DT8 85063 DIM5 B-B

30715 8035 B-B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐


203 99 56 ANO CABLE BASE S ANO

☐

203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Fixation components



30710 0020 B INF40 SQ 320/360 - SUSPENSION SET 1,6m B

☐

30710 0020 W INF40 SQ 320/360 - SUSPENSION SET 1,6m W

☐


30710 0040 B INF40 SQ 320/360 - SUSPENSION SET 3,0m B

☐

30710 0040 W INF40 SQ 320/360 - SUSPENSION SET 3,0m W

☐

INFORM 40 SQ 320 DOWN TW 1 DT8 85063 DIM5 B-B

30715 8035 B-B

Notes: