





INFORM 40 SQ 320 DOWN-UP TW 1 DT8 85063 DIM5 B-B

30725 8035 B-B

AVAILABLE IN
BLACK-BLACK 30725 8035 B-B
WHITE-BLACK 30725 8035 W-B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5,3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) 1 driver for DOWN and UP INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm² 1,6m MELANOPIC LIGHT TECHNOLOGY
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm UP @ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or DOWN @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm UP @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 3904lm // 29,8W // 131lm/W UP @ 2700K: 3904lm // 29,8W // 131lm/W Or DOWN @ 5000K: 4672lm // 27W // 173lm/W UP @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 2701lm // 34W // 79lm/W UP @ 2700K: 2571lm // 34W // 75lm/W Or DOWN @ 5000K: 3233lm // 31W // 104lm/W UP @ 5000K: 3077lm // 31W // 99lm/W

INFORM 40 SQ 320 DOWN-UP TW 1 DT8 85063 DIM5 B-B
30725 8035 B-B



Options

CABLE BASE R/S

For detailed installation instructions, please consult the manual: [30725_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Notes: