





LOGIC LINEAR 880 WALLGRAZER 927 DIM5 INOX

30822 9205 INOX

AVAILABLE IN
INOX 30822 9205 INOX



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	4.4
ADJUSTABILITY	non adjustable
INFORMATION	16 x WALLGRAZER LENS INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H07 RN-F 5 x 1mm ² 0,5m INCL.IP68 CONNECTOR 5P ESG 8mm max.500kg

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 50) / 2700K / 3288lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	3288lm // 28,8W // 111lm/W
LED TECHNICS (LUMINAIRE)	1879lm // 33W // 57lm/W

Requirements

LOGIC LINEAR BOX


LOGIC LINEAR 880 WALLGRAZER 927 DIM5 INOX

30822 9205 INOX

For detailed installation instructions, please consult the manual: [30822_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Ground mounting boxes



30810 0030 LOGIC LINEAR 880 BOX

☐

Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P

☐

Notes: