



FRAX MB 930 LINEAR H FBRX



26010 9340 FBRX

AVAILABLE IN

FLEMISH BRONZE OUTDOOR 26010 9340 FBRX

ANTHRACITE (DARK GREY) 26010 9340 N

PINE GREEN 26010 9340 PGR



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.1
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC INCL.LINEAR SPREAD LENS HORIZONTAL Oval spread 15°-60° INCL.1 x CABLE H05 RN-F 3 x 1mm ² 2m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 64) / 3000K / 2654lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	2654lm // 23,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	1858lm // 27W // 69lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

FRAX MB 930 LINEAR H FBRX

26010 9340 FBRX

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP

For detailed installation instructions, please consult the manual: [26010_XX40_HAND.pdf](#)

FRAX MB 930 LINEAR H FBRX

26010 9340 FBRX

FINISH YOUR SPECIFICATION

Pins and plates for bollards



26070 0040 FBRX FRAX PIN FBRX

☐


26070 0040 N FRAX PIN N

☐

26070 0040 PGR FRAX PIN PGR

☐

Fixation components



26070 0060 FBRX FRAX BRACKET FBRX

☐


26070 0060 N FRAX BRACKET N

☐

26070 0060 PGR FRAX BRACKET PGR

☐

Light altering devices




26070 0020 N FRAX M KAP N

☐


FRAX MB 930 LINEAR H FBRX

26010 9340 FBRX

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26070 0050 N FRAX STRAP N

☐

Notes: