





FRAX MB POLE 927 LINEAR V N
26022 9200 N

AVAILABLE IN
ANTHRACITE (DARK GREY) 26022 9200 N



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC INCL.LINEAR SPREAD LENS VERTICAL Oval spread 60°-15° INCL.1 x CABLE H05 RN-F 3 x 1mm² 6m
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2423lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	2423lm // 23,4W // 103lm/W
LED TECHNICS (LUMINAIRE)	1696lm // 27W // 63lm/W

Requirements
FRAX BRACKET
Options
FRAX ANTI VANDAL SCREWS

FRAX MB POLE 927 LINEAR V N

26022 9200 N


Accessories

FRAX M KAP

For detailed installation instructions, please consult the manual: [26022_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices




26070 0020 N FRAX M KAP N

☐


Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26071 0050 N FRAX POLE 60 BRACKET N

☐

26071 0060 N FRAX POLE 80 BRACKET N

☐

Notes: