





FRAX MB POLE SUPERSPOT 92708
HONEYCOMB N
26026 9210 N

AVAILABLE IN
ANTHRACITE (DARK GREY) 26026 9210 N



 [View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	7 x LENS SP-8° INCL.LED POWER SUPPLY 900mA-DC INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm² 6m

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 18,2W / CRI>90 (R9: 50) / 2700K / 1884lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	1884lm // 18,2W // 103lm/W
LED TECHNICS (LUMINAIRE)	1432lm // 21W // 68lm/W

Requirements	
FRAX BRACKET	

Options	
FRAX ANTI VANDAL SCREWS	


FRAX MB POLE SUPERSPOT 92708 HONEYCOMB N
26026 9210 N

Accessories
FRAX M KAP

For detailed installation instructions, please consult the manual: [26026_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices



26070 0020 N FRAX M KAP N


☐

Other




26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐



26071 0050 N FRAX POLE 60 BRACKET N

☐



26071 0060 N FRAX POLE 80 BRACKET N

☐

Notes: