




FRAX S SUPERSPOT 92708
HONEYCOMB A
26101 9220 A

AVAILABLE IN
ALU GREY 26101 9220 A
FLEMISH BRONZE OUTDOOR 26101 9220 FBRX
ANTHRACITE (DARK GREY) 26101 9220 N



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.5
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	3 x LENS SP-8° INCL.LED POWER SUPPLY 700mA-DC INCL.HONEYCOMB

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6W / CRI>90 (R9: 50) / 2700K / 659lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	659lm // 6W // 110lm/W
LED TECHNICS (LUMINAIRE)	540lm // 7W // 78lm/W

Options	
FRAX ANTI VANDAL SCREWS	

Accessories	
FRAX S KAP	


FRAX S SUPERSPOT 92708 HONEYCOMB A

26101 9220 A

For detailed installation instructions, please consult the manual: [26101_XX20_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices



26070 0010 N FRAX S KAP N

☐

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

Notes: