





KIX II PIN 927 A

13536 9200 A

AVAILABLE IN
ALU GREY 13536 9200 A
ANTHRACITE (DARK GREY) 13536 9200 N
PINE GREEN 13536 9200 PGR



 [View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.2
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	INCL.1 x CABLE H05 RN-F 2 x 1mm ² 2m INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	576lm // 7W // 86lm/W

Options

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P



Accessories

KAP KIX
HONEYCOMB KIX



For detailed installation instructions, please consult the manual: [13536_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Waterproof connection parts

	216 12 00 CBOX	☐
	216 12 01 IP68 CONNECTION KIT	☐
	216 12 02 IP68 CONNECTOR 3P	☐

Light altering devices

	232 10 00 N KAP KIX N	☐
	232 10 03 N HONEYCOMB KIX N	☐

Notes: