





KIX S PIN 24V 92710 N

13529 9210 N

AVAILABLE IN
ANTHRACITE (DARK GREY) 13529 9210 N
PINE GREEN 13529 9210 PGR



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.3
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	LENS 10° INCL.1 x CABLE H05 RN-F 2 x 1 mm ² 2m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output)

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2W / CRI>90 (R9: 55) / 2700K / 220lm
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	220lm // 2W // 110lm/W
LED TECHNICS (LUMINAIRE)	157lm // 2W // 68lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P



KIX S PIN 24V 92710 N

13529 9210 N


For detailed installation instructions, please consult the manual: [**13529_XXX0_HAND.pdf**](#)

KIX S PIN 24V 92710 N

13529 9210 N


FINISH YOUR SPECIFICATION

LED power supplies #



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W

75


☐

21012 0160 LED POWER SUPPLY 24V-DC / 24W

12

☐


Miscellaneous control equipment




21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)

☐

Waterproof connection parts



216 12 00 CBOX

☐

216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐



KIX S PIN 24V 92710 N

13529 9210 N

Notes: