





LOGIC 60 R A SP 24V 93006 ANO
13961 9310 ANO

AVAILABLE IN
ALU ANODIZED 13961 9310 ANO
BLACK 13961 9310 B



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 61
RECESSED DEPTH (MM)	100
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	LENS SP-6° INCL.1 x CABLE H05 RN-F 2 x 1mm² 0,5m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output) IEC 60598-2-13 : max.150kg 25N/cm² ESG 5mm

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2W / CRI>90 / 3000K / 229lm
SDCM	SDCM3
RISKGROUP	RG2 (threshold 0,6m)
LED TECHNICS (LIGHT SOURCE)	229lm // 2W // 115lm/W
LED TECHNICS (LUMINAIRE)	219lm // 2W // 95lm/W

Requirements

LED POWER SUPPLY 24V-DC

LOGIC 60 R A SP 24V 93006 ANO

13961 9310 ANO

Options

LOGIC 60 BOX R

CBOX

IP68 CONNECTION KIT


IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [13961_XXX0_HAND.pdf](#)

LOGIC 60 R A SP 24V 93006 ANO
13961 9310 ANO


FINISH YOUR SPECIFICATION

LED power supplies #



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W


75 ☐



21012 0160 LED POWER SUPPLY 24V-DC / 24W

12 ☐


Miscellaneous control equipment



21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)

☐

Ground mounting boxes






213 19 10 LOGIC 60 BOX R

☐

LOGIC 60 R A SP 24V 93006 ANO

13961 9310 ANO

Waterproof connection parts

	216 12 00 CBOX	☐
	216 12 01 IP68 CONNECTION KIT	☐
	216 12 02 IP68 CONNECTOR 3P	☐

Notes: