





LOGIC 60 R WALLWASH SBL 930 ANO

13979 9300 ANO

AVAILABLE IN
ALU ANODIZED 13979 9300 ANO



 [View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 61
RECESSED DEPTH (MM)	100
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.CABLE H05 RN-F 2 x 1mm² 0,5m EXCL.LED POWER SUPPLY 24V-DC IEC 60598-2-13 : max.150kg 25N/cm² ESG 5mm

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 4W / CRI>90 / 3000K / 372lm
LED TECHNICS (LIGHT SOURCE)	372lm // 4W //93lm/W
LED TECHNICS (LUMINAIRE)	155lm // 5W // 34lm/W

Requirements	
LED POWER SUPPLY 24V-DC	

Options	
LOGIC 60 BOX R	
CBOX	
IP68 CONNECTION KIT	
IP68 CONNECTOR 3P	



LOGIC 60 R WALLWASH SBL 930 ANO

13979 9300 ANO

For detailed installation instructions, please consult the manual: [**13979_XXX0_HAND.pdf**](#)


LOGIC 60 R WALLWASH SBL 930 ANO

13979 9300 ANO

FINISH YOUR SPECIFICATION


LED power supplies

#



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W

33


☐


21012 0160 LED POWER SUPPLY 24V-DC / 24W

5

☐


Ground mounting boxes




213 19 10 LOGIC 60 BOX R

☐

Waterproof connection parts



216 12 00 CBOX

☐


216 12 01 IP68 CONNECTION KIT

☐


216 12 02 IP68 CONNECTOR 3P

☐

LOGIC 60 R WALLWASH SBL 930 ANO

13979 9300 ANO

Notes: