





LOGIC LINEAR ON 440 WALLGRAZER AG 927 DIM5 A 30830 9205 A

AVAILABLE IN
ALU GREY 30830 9205 A
BLACK 30830 9205 B
FLEMISH BRONZE OUTDOOR 30830 9205 FBRX
ANTHRACITE (DARK GREY) 30830 9205 N
WHITE 30830 9205 W



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
INFORMATION	8 x WALLGRAZER LENS + ANTI GLARE SHIELD EXCL. LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 50) / 2700K / 1644lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	1644lm // 14,4W // 111lm/W
LED TECHNICS (LUMINAIRE)	784lm // 17W // 47lm/W

Requirements

WALL BRACKET SET
 FLOOR BRACKET SET
 IP68 CABLE + CONNECTOR 5P
 LED POWER SUPPLY 48V-DC

LOGIC LINEAR ON 440 WALLGRAZER AG 927 DIM5 A

30830 9205 A

Options


THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual: [30830_XXX5_HAND.pdf](#)

LOGIC LINEAR ON 440 WALLGRAZER AG 927 DIM5 A
30830 9205 A

FINISH YOUR SPECIFICATION

LED power supplies #



21032 0390 LED POWER SUPPLY 48V-DC / 90W

5

Fixation components




30810 0040 INOX WALL BRACKET SET 60 INOX

30810 0040 N WALL BRACKET SET 60 N



30810 0050 INOX WALL BRACKET SET 100 INOX



30810 0060 INOX WALL BRACKET SET 200 INOX



30810 0070 INOX FLOOR BRACKET SET INOX

⌵ DELTALIGHT®

LOGIC LINEAR ON 440 WALLGRAZER AG 927 DIM5 A

30830 9205 A

Electric connection parts

	30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m	☐
	30810 0090 IP68 CABLE + CONNECTOR 5P - 2m	☐
	30810 0100 THROUGH WIRING SET IP68 440	☐

Notes: