



LOGIC LINEAR ON 880 92715 DIM5 A

30835 9215 A

AVAILABLE IN



ALU GREY 30835 9215 A

BLACK 30835 9215 B

FLEMISH BRONZE OUTDOOR 30835 9215 FBRX

ANTHRACITE (DARK GREY) 30835 9215 N

WHITE 30835 9215 W



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2
INFORMATION	16 x LENS SP-15° EXCL. LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 50) / 2700K / 3288lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	3288lm // 28,8W // 111lm/W
LED TECHNICS (LUMINAIRE)	2880lm // 33W // 87lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

LOGIC LINEAR ON 880 92715 DIM5 A

30835 9215 A

Options

THROUGH WIRING SET IP68




For detailed installation instructions, please consult the manual: [30835_XXX5_HAND.pdf](#)

 DELTALIGHT®

LOGIC LINEAR ON 880 92715 DIM5 A

30835 9215 A

FINISH YOUR SPECIFICATION

LED power supplies		#
	21032 0390 LED POWER SUPPLY 48V-DC / 90W	2 ☐
Fixation components		
	30810 0040 INOX WALL BRACKET SET 60 INOX	☐
	30810 0040 N WALL BRACKET SET 60 N	☐
	30810 0050 INOX WALL BRACKET SET 100 INOX	☐
	30810 0060 INOX WALL BRACKET SET 200 INOX	☐
	30810 0070 INOX FLOOR BRACKET SET INOX	☐

LOGIC LINEAR ON 880 92715 DIM5 A
30835 9215 A

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m

☐

30810 0090 IP68 CABLE + CONNECTOR 5P - 2m

☐

30810 0110 THROUGH WIRING SET IP68 880

☐

Notes: