





OBLIX F 100 927 A

15116 9200 A

AVAILABLE IN

ALU GREY 15116 9200 A

ANTHRACITE (DARK GREY) 15116 9200 N



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	4.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	757lm // 10W // 77lm/W

Options	
PIN 18	
CBOX	
IP68 CONNECTION KIT	
IP68 CONNECTOR 3P	


OBLIX F 100 927 A

15116 9200 A


For detailed installation instructions, please consult the manual: [15116_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

☐

216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



15222 0180 PIN 18

☐

Notes: