





OBLIX F 70 927 A

15115 9200 A

AVAILABLE IN
ALU GREY 15115 9200 A
ANTHRACITE (DARK GREY) 15115 9200 N



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	3,7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	757lm // 10W // 77lm/W



Options

- PIN 18
- CBOX
- IP68 CONNECTION KIT
- IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [15115_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Waterproof connection parts

	216 12 00 CBOX	☐
	216 12 01 IP68 CONNECTION KIT	☐
	216 12 02 IP68 CONNECTOR 3P	☐

Pins and plates for bollards

	15222 0180 PIN 18	☐
---	--------------------------	--------------------------

Notes: