





POLESANO 930 FLOOD A-B

43 11 933 A-B

AVAILABLE IN

ALU GREY-BLACK 43 11 933 A-B

ANTHRACITE (DARK GREY)-BLACK 43 11 933 N-B



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP66
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	5
ADJUSTABILITY	360° swiveling, 360° rotatable
INFORMATION	16 x REFLECTOR WFL-70° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC $\lambda > 0,9$ Inrush current : 32A - 355μs @ 230V-AC Max. 10 units on circuit breaker B 16A @ 230V-AC (13 units on B 20A)

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, ENEC+, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 41,6W / CRI>90 (R9: 64) / 3000K / 4718lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	4718lm // 41,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	3381lm // 48W // 71lm/W

Remarks

Take a look at the POLESANO brochure

Requirements

POLESANO POLE

POLESANO 930 FLOOD A-B

43 11 933 A-B

Accessories

HONEYCOMB S105

LINEAR SPREAD LENS S105


For detailed installation instructions, please consult the manual: [43_XX_XXX-431_X00_XX1_\(X\)X1_HAND.pdf](#)

POLESANO 930 FLOOD A-B


43 11 933 A-B

FINISH YOUR SPECIFICATION

Light altering devices



431 03 01 B HONEYCOMB S105 B

☐







431 03 02 LINEAR SPREAD LENS S105

☐

POLESANO 930 FLOOD A-B








43 11 933 A-B

Pole

	431 400 111 11 A	POLESANO 4M - 1 ANCHORED A	☐
	431 400 111 11 N	POLESANO 4M - 1 ANCHORED N	☐
	431 400 111 31 A	POLESANO 4M - 3 ANCHORED A	☐
	431 400 111 31 N	POLESANO 4M - 3 ANCHORED N	☐
	431 400 111 41 A	POLESANO 4M - 4 ANCHORED A	☐
	431 400 111 41 N	POLESANO 4M - 4 ANCHORED N	☐
	431 400 111 211 A	POLESANO 4M - 21L ANCHORED A	☐
	431 400 111 211 N	POLESANO 4M - 21L ANCHORED N	☐
	431 400 111 221 A	POLESANO 4M - 22L ANCHORED A	☐
	431 400 111 221 N	POLESANO 4M - 22L ANCHORED N	☐
	431 400 221 11 A	POLESANO 4M - 1 BASE A	☐
	431 400 221 11 N	POLESANO 4M - 1 BASE N	☐







POLESANO 930 FLOOD A-B

43 11 933 A-B

	431 400 221 31 A POLESANO 4M - 3 BASE A	☐
	431 400 221 31 N POLESANO 4M - 3 BASE N	☐
	431 400 221 41 A POLESANO 4M - 4 BASE A	☐
	431 400 221 41 N POLESANO 4M - 4 BASE N	☐
	431 400 221 211 A POLESANO 4M - 21L BASE A	☐
	431 400 221 211 N POLESANO 4M - 21L BASE N	☐
	431 400 221 221 A POLESANO 4M - 22L BASE A	☐
	431 400 221 221 N POLESANO 4M - 22L BASE N	☐
	431 600 121 11 A POLESANO 6M - 1 ANCHORED A	☐
	431 600 121 11 N POLESANO 6M - 1 ANCHORED N	☐
	431 600 121 31 A POLESANO 6M - 3 ANCHORED A	☐
	431 600 121 31 N POLESANO 6M - 3 ANCHORED N	☐
	431 600 121 41 A POLESANO 6M - 4 ANCHORED A	☐


POLESANO 930 FLOOD A-B

43 11 933 A-B

	<u>431 600 121 41 N</u>	POLESANO 6M - 4 ANCHORED N	☐
	<u>431 600 121 211 A</u>	POLESANO 6M - 21L ANCHORED A	☐
	<u>431 600 121 211 N</u>	POLESANO 6M - 21L ANCHORED N	☐
	<u>431 600 121 221 A</u>	POLESANO 6M - 22L ANCHORED A	☐
	<u>431 600 121 221 N</u>	POLESANO 6M - 22L ANCHORED N	☐
	<u>431 600 321 11 A</u>	POLESANO 6M - 1 BASE A	☐
	<u>431 600 321 11 N</u>	POLESANO 6M - 1 BASE N	☐
	<u>431 600 321 31 A</u>	POLESANO 6M - 3 BASE A	☐
	<u>431 600 321 31 N</u>	POLESANO 6M - 3 BASE N	☐
	<u>431 600 321 41 A</u>	POLESANO 6M - 4 BASE A	☐
	<u>431 600 321 41 N</u>	POLESANO 6M - 4 BASE N	☐
	<u>431 600 321 211 A</u>	POLESANO 6M - 21L BASE A	☐
	<u>431 600 321 211 N</u>	POLESANO 6M - 21L BASE N	☐

POLESANO 930 FLOOD A-B

43 11 933 A-B



431 600 321 221 A POLESANO 6M - 22L BASE A

☐

431 600 321 221 N POLESANO 6M - 22L BASE N

☐

Notes: