





SL19 - SPY 39 WALLWASH 927 MDL B

27038 9200 B

AVAILABLE IN
BLACK 27038 9200 B
FLEMISH BRONZE 27038 9200 FBR
FLEMISH GOLD 27038 9200 FG
GOLD COLOURED 27038 9200 GC
WHITE 27038 9200 W



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	WALLWASH LENS EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	413lm // 7W // 62lm/W

Requirements	
	LED POWER SUPPLY 48V-DC

Options	
	DIMMABLE MODULATOR

SL19 - SPY 39 WALLWASH 927 MDL B


27038 9200 B

For detailed installation instructions, please consult the manual: [27038_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

19




300 90 012 SMART 48 MODULATOR WD

19


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20


SL19 - SPY 39 WALLWASH 927 MDL B

27038 9200 B

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile

Available Colours



27011 0060 SL19 - PROFILE 3m



Notes: