





SPIX P70-2 92710 N

29717 9210 N

AVAILABLE IN
ANTHRACITE (DARK GREY) 29717 9210 N
PINE GREEN 29717 9210 PGR



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK05
WEIGHT (KG)	1.8
ADJUSTABILITY	90° swiveling, 360° rotatable
INFORMATION	LENS 10° INCL.LED POWER SUPPLY 700mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 2W / CRI>90 (R9: 55) / 2700K / 220lm)
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	440lm // 4W // 110lm/W
LED TECHNICS (LUMINAIRE)	346lm // 5W // 75lm/W

Requirements

PIN 11
PLATE 12

Options




CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

SPIX P70-2 92710 N
 29717 9210 N



For detailed installation instructions, please consult the manual: [29717_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Waterproof connection parts

	216 12 00 CBOX	☐
	216 12 01 IP68 CONNECTION KIT	☐
	216 12 02 IP68 CONNECTOR 3P	☐

Pins and plates for bollards

	229 01 11 PIN 11	☐
	15223 0120 N PLATE 12 N	☐

Notes: