



D-LINER 30 INF SAPP 11 93067 DIM5 B-B

29115 9325 B-B



AVAILABLE IN

BLACK-BLACK 29115 9325 B-B

BLACK-FLEMISH GOLD 29115 9325 B-FG

WHITE-BLACK 29115 9325 W-B

WHITE-WHITE 29115 9325 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° INCL.DIMMABLE LED POWER SUPPLY 600mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 1m + WIELAND PLUG 5 POLE INCL.2 x SUSPENSION BRACKET SAPP

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3086lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3086lm // 22,3W // 138lm/W
LED TECHNICS (LUMINAIRE)	2694lm // 26W // 105lm/W

For detailed installation instructions, please consult the manual: [29115_XXX5_HAND.pdf](#)

D-LINER 30 INF SAPP 11 93067 DIM5 B-B
29115 9325 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling SAPP	-

Notes: