



D-LINER 30 INF 30BD 11 RD 93067 B-B

29118 9320 B-B



AVAILABLE IN

BLACK-BLACK 29118 9320 B-B

BLACK-FLEMISH GOLD 29118 9320 B-FG

WHITE-BLACK 29118 9320 W-B

WHITE-WHITE 29118 9320 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 400/600mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 1m + WIELAND PLUG 2 POLE INCL.2 x SUSPENSION BRACKET 30BD

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,1-22,3W / CRI>90 (R9: 50) / 3000K / 2136-3086lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3086lm // 22,3W // 138lm/W
LED TECHNICS (LUMINAIRE)	2694lm // 26W // 105lm/W

Requirements

INFORM POWER SUPPLY 25W


D-LINER 30 INF 30BD 11 RD 93067 B-B
 29118 9320 B-B

For detailed installation instructions, please consult the manual: [29118_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

LED power supplies	#
 25510 0395 INFORM POWER SUPPLY 25W DIM5	1 ☐

Notes: