





**D-LINER 19 INF SAPP/30BD 11 RD
93067 B**

29130 9320 B

AVAILABLE IN
BLACK 29130 9320 B



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR WFL-67° EXCL.LED POWER SUPPLY 400/600mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 1m + WIELAND PLUG 2 POLE INCL.2 x BUTTERFLY BRACKET SAPP/30BD

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,1-22,3W / CRI>90 (R9: 50) / 3000K / 2136-3086lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3086lm // 22,3W // 138lm/W
LED TECHNICS (LUMINAIRE)	2680lm // 26W // 105lm/W

Requirements

INFORM POWER SUPPLY 25W


For detailed installation instructions, please consult the manual: [29130_XXX0_HAND.pdf](#)

D-LINER 19 INF SAPP/30BD 11 RD 93067 B
 29130 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

LED power supplies	#
 25510 0395 INFORM POWER SUPPLY 25W DIM5	1 ☐

Notes: