





D-LINER 19 INF SAPP/30BD 13 RD
93067 B

29131 9320 B

AVAILABLE IN
BLACK 29131 9320 B



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR WFL-67° EXCL.LED POWER SUPPLY 500/750mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 1m + WIELAND PLUG 2 POLE INCL.2 x BUTTERFLY BRACKET SAPP/30BD

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,6-27,9W / CRI>90 (R9: 50) / 3000K / 2670-3858lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3858lm // 27,9W // 138lm/W
LED TECHNICS (LUMINAIRE)	3350lm // 32W // 104lm/W

Requirements	
INFORM POWER SUPPLY 45W	


For detailed installation instructions, please consult the manual: [29131_XXX0_HAND.pdf](#)

D-LINER 19 INF SAPP/30BD 13 RD 93067 B
 29131 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

LED power supplies	#
 25510 0385 INFORM POWER SUPPLY 45W DIM5	1 ☐

Notes: