





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 360 DOWN-UP
93063 DIM5 B-B
30735 9335 B-B

AVAILABLE IN
BLACK-BLACK 30735 9335 B-B
WHITE-BLACK 30735 9335 W-B



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5,9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver DALI DT6 : DOWN & UP on separate channels INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m

Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

INFORM 40 SQ 360 DOWN-UP 93063 DIM5 B-B

30735 9335 B-B

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm UP (HO): LED cluster 60,5W / CRI>90 (R9: 50) / 3000K / 8736lm Or DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm UP: LED cluster 41,8W / CRI>90 (R9: 50) / 3000K / 6464lm
TM-30 VALUES	Rf: 92 / Rg: 100 DOWN: rf: 92 / Rg: 100 UP: rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000 L90 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 6989lm // 48,4W // 145lm/W UP (HO): 8736lm // 60,5W // 145lm/W Or DOWN: 5069lm // 32,6W // 155lm/W UP: 6464lm // 41,8W // 155lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 4836lm // 56W // 87lm/W UP (HO): 5753lm // 70W // 83lm/W Or DOWN: 3507lm // 37W // 94lm/W UP: 4257lm // 48W // 89lm/W

Options


CABLE BASE R / S

For detailed installation instructions, please consult the manual: [30735_XXX5_HAND.pdf](#)

INFORM 40 SQ 360 DOWN-UP 93063 DIM5 B-B
30735 9335 B-B

FINISH YOUR SPECIFICATION

Current supply

	☐ <u>203 99 55 ANO</u> CABLE BASE R ANO
	☐ <u>203 99 55 B</u> CABLE BASE R B
	☐ <u>203 99 55 W</u> CABLE BASE R W
	☐ <u>203 99 56 ANO</u> CABLE BASE S ANO
	☐ <u>203 99 56 B</u> CABLE BASE S B
	☐ <u>203 99 56 W</u> CABLE BASE S W

Notes: