





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 360 PDS DOWN-UP
93063 DIM5 B-B
30736 9335 B-B

AVAILABLE IN
BLACK-BLACK 30736 9335 B-B
WHITE-BLACK 30736 9335 W-B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5,9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m

Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

INFORM 40 SQ 360 PDS DOWN-UP 93063 DIM5 B-B

30736 9335 B-B

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm UP (HO): LED cluster 60,5W / CRI>90 (R9: 50) / 3000K / 8736lm Or DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm UP: LED cluster 41,8W / CRI>90 (R9: 50) / 3000K / 6464lm
TM-30 VALUES	Rf: 92 / Rg: 100 DOWN: rf: 92 / Rg: 100 UP: rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000 L90 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 6989lm // 48,4W // 145lm/W UP (HO): 8736lm // 60,5W // 145lm/W Or DOWN: 5069lm // 32,6W // 155lm/W UP: 6464lm // 41,8W // 155lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 4836lm // 56W // 87lm/W UP (HO): 5753lm // 70W // 83lm/W Or DOWN: 3507lm // 37W // 94lm/W UP: 4257lm // 48W // 89lm/W



Options

CABLE BASE R / S



For detailed installation instructions, please consult the manual: [30736_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Other

	26510 0010 PDS REMOTE CONTROL	☐
	26510 0020 PDS SENSOR PROGRAMMER	☐

Notes: