





INFORM SQ P144-3 DOWN-UP 92767 B-B

25512 9220 B-B

AVAILABLE IN
BLACK-BLACK 25512 9220 B-B
BLACK-FLEMISH GOLD 25512 9220 B-FG
WHITE-BLACK 25512 9220 W-B
WHITE-WHITE 25512 9220 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	36 x REFLECTOR FL-67° (DOWN) EXCL.LED POWER SUPPLY 700mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm UP: LED cluster 14,1W / CRI>90 (R9: 50) / 2700K / 2026lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 1519lm // 10,5W // 144lm/W UP: 2026lm // 14,1W // 144lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1288lm // 12W // 107lm/W UP: 1366lm // 16W // 84lm/W

Requirements

INFORM SQ POWERBOX 50W (DIM5)
 INFORM POWER SUPPLY 45W + SUSPENSION+CONNECTION ST



INFORM SQ P144-3 DOWN-UP 92767 B-B

25512 9220 B-B

For detailed installation instructions, please consult the manual: [25512_XXX0_HAND.pdf](#)


INFORM SQ P144-3 DOWN-UP 92767 B-B

25512 9220 B-B

FINISH YOUR SPECIFICATION

Power box

#




25510 0010 B INFORM SQ POWERBOX 50W B

1

☐

25510 0010 W INFORM SQ POWERBOX 50W W

1

☐


25510 0015 B INFORM SQ POWERBOX 50W DIM5 B

1

☐


25510 0015 W INFORM SQ POWERBOX 50W DIM5 W

1

☐


LED power supplies

#



25510 0385 INFORM POWER SUPPLY 45W DIM5

1

☐



25510 0430 INFORM POWER SUPPLY 45W

1

☐

Electric connection parts

#



15225 0350 B SUSPENSION + CONNECTION ST B

2 needed

☐

15225 0350 W SUSPENSION + CONNECTION ST W

2 needed

☐



INFORM SQ P144-3 DOWN-UP 92767 B-B

25512 9220 B-B

Notes: