



## SOLI - FORM 60 92767 MDL B-B

27127 9220 B-B



AVAILABLE IN

**BLACK-BLACK** 27127 9220 B-B

**BLACK-FLEMISH GOLD** 27127 9220 B-FG

**WHITE-BLACK** 27127 9220 W-B

**WHITE-WHITE** 27127 9220 W-W



 [View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.24 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 11,2W / CRI>90 (R9: 50) / 2700K / 1464lm
<b>TM-30 VALUES</b>	Rf: 93 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 60000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1464lm // 11,2W // 131lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1278lm // 13W // 99lm/W

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR


**SOLI - FORM 60 92767 MDL B-B**

27127 9220 B-B

For detailed installation instructions, please consult the manual: [27127\\_XXX0\\_HAND.pdf](#)


**FINISH YOUR SPECIFICATION**

**SMART 48** #



**300 90 011** SMART 48 MODULATOR DIM9


16



**300 90 012** SMART 48 MODULATOR WD


16

**LED power supplies** #




**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

20



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

8



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

17


**SOLI - FORM 60 92767 MDL B-B**

27127 9220 B-B


**COMPATIBLE COMPOSABLES**

**SOLISCAPE profile**

**Available Colours**



**27111 0020** SOLI - PROFILE 2m



**27111 0030** SOLI - PROFILE 3m



Notes:

Empty rectangular box for notes.