

SOLI - FORM 110 92767 MDL B-B

27129 9220 B-B



AVAILABLE IN

BLACK-BLACK 27129 9220 B-B

BLACK-FLEMISH GOLD 27129 9220 B-FG

WHITE-BLACK 27129 9220 W-B

WHITE-WHITE 27129 9220 W-W



[View on website](#)

General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.9 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | INCL.48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC |

Electrical info

| | |
|---------------------|------------------------------------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | MDL = 1-10V or DALI or push button |
| ENERGY CLASS | E |
| CERTIFICATES | CB, ENEC |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 22,3W / CRI>90 (R9: 50) / 2700K / 2928lm |
| TM-30 VALUES | Rf: 93 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | 2928lm // 22,3W // 131lm/W |
| LED TECHNICS (LUMINAIRE) | 2556lm // 26W // 100lm/W |

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

SOLI - FORM 110 92767 MDL B-B


27129 9220 B-B

For detailed installation instructions, please consult the manual: [27129_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

7




300 90 012 SMART 48 MODULATOR WD

7


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

4




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

9



21012 0230 LED POWER SUPPLY 48V-DC / 100W

4



21012 0240 LED POWER SUPPLY 48V-DC / 200W

8


SOLI - FORM 110 92767 MDL B-B

27129 9220 B-B


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m



Notes: