





## SOLI - FORM 90 DOWN-UP 1 CIRCUIT 92767 DIM5 B-B

27141 9225 B-B

AVAILABLE IN  
**BLACK-BLACK** 27141 9225 B-B  
**BLACK-FLEMISH GOLD** 27141 9225 B-FG  
**WHITE-BLACK** 27141 9225 W-B  
**WHITE-WHITE** 27141 9225 W-W



 [View on website](#)

General info	
<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC 1 CIRCUIT

Electrical info	
<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

Lightsource info	
<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	DOWN: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm UP: LED cluster 10,5W / CRI>90 (R9: 50) / 2700K / 1519lm
<b>TM-30 VALUES</b>	Rf: 93 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 60000
<b>LED TECHNICS (LIGHT SOURCE)</b>	DOWN: 1519lm // 10,5W // 144lm/W UP: 1519lm // 10,5W // 144lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	DOWN: 1291lm // 12W // 107lm/W UP: 1018lm // 12W // 84lm/W

Requirements	
LED POWER SUPPLY 48V-DC	

# SOLI - FORM 90 DOWN-UP 1 CIRCUIT 92767 DIM5 B-B


27141 9225 B-B

For detailed installation instructions, please consult the manual: [27141\\_XXX5\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION


### LED power supplies

#




**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

4




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

10



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

4




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

8


## COMPATIBLE COMPOSABLES

### SOLISCAPE profile

Available Colours



**27111 0020** SOLI - PROFILE 2m



**27111 0030** SOLI - PROFILE 3m





**SOLI - FORM 90 DOWN-UP 1 CIRCUIT 92767 DIM5 B-B**

27141 9225 B-B

Notes: